



Galvanized Coat Rods are made of $\frac{3}{8}$ " diameter galvanized steel. Use in place of double-prong ceiling hooks.

Coat Hooks

are zinc plated steel rod stock with ball points for snag free use.



Galvanized Lockers are for installations in high corrosive atmospheres. Lockers are fabricated from galvanized steel and have standard enamel finish. *Not available for expanded metal lockers.*



Recess Trim closes spaces at top and ends of recessed lockers with finishing strips and splice caps.



Fire Extinguisher Lockers are available with or without "waste" panel. (Extinguisher and decal not included.)



Bottom Options are galvanized, stainless (not painted) and plastic.



Aluminum Number Plates with clearly etched numbers are 2 $\frac{1}{2}$ "w x 1" h, fit pre punched holes in locker doors.



Tamper Guard Handles are standard on single, double, triple tier lockers. Provides a slim profile and clear access to locks.



Zinc Alloy Recessed Handles have light grain nickel plated finish. Finger lift activates door lock. Used with all lock options.



Single Point Latch System operates with no moving parts. Available latches for built-in locks with wrap around technology.



Lock Options can be used with all handles, and retro-fitted to existing installations.



Roll Point Catches add convenience to multiple tier lockers. One point door catch has padlock hasp.



Extra Shelves are formed from a single sheet of steel flanged on all four sides for strength with safety front edge.



Locker Legs add 6" to over-all locker height. Must be specified on initial order.