

Steel Lockers

Six Tier Multi-User Employee Lockers

Lyon multi-user lockers with Digilock SES locks allow employee lockers to be shared by multiple shifts, therefore reducing the number of lockers and real estate required for the lockers, while providing a significant deterrent to employee theft.

- Lockers can be audited by using the management bypass key
- Lockers can be shared between shifts
- Digital locks are programmed to unlock after 12 hours of non-operation
- Shipped set up

W x D x H* (per locker opening)	No. of Frames	No. of Openings	Cat. No.
Six Tier			
12" x 12" x 12"	1	6	PP5332RLSU
12" x 12" x 12"	3	18	PP5332-3RLSU
12" x 18" x 12"	1	6	PP5362RLSU
12" x 18" x 12"	3	18	PP5362-3RLSU

*Heights shown do not include legs – add 6" to height for legs.



ACCESSORIES AND RELATED PRODUCTS

Management Key

- Initializes the digital locks
- Allows simple access for management to open Digilock SES locks, if required
- Provides external power to the lock if batteries fail

No. 7029



Color Selection

In Stock
PP Putty



Additional colors are available upon request



For additional accessories, see pages 114-115

Features



With Digilock, when a lock is unlocked, it is considered available and can be locked with any 4-digit code by any employee. Digital locks are programmed to unlock after 12 hours of non-use to prevent a user from taking over a locker after a shift.

- **Loss Prevention** - Lockers can be audited by using the management bypass key
- **Shared use** - Lockers can be shared between shifts
- **Reduces** the total number of lockers required at a facility
- Digital locks are **programmed to unlock** after 12 hours of non-operation
- **Low cost** retail solution that quickly pays for itself within the first few months of implementation
- Helps **deter employee theft** as lockers can be audited at any time without disturbing the user code
- **Eliminates** lost keys, unavailable lockers, bolt cutters and the waste of management's time

NOTE: In the interest of safety, Lyon strongly recommends that lockers be floor and/or wall anchored. See page 114 for important locker anchoring information.