

FLAMMABLE SAFETY CABINETS

Protection for Your Employees and Property

Flammable Safety Cabinets provide protection for your employees and property with proper storage of flammable liquids. Available with Manual or Self-Closing doors.

Specifications:

- Fully welded construction with 18-gauge double wall construction with 1-1/2" insulating airspace
- Flush-mounted paddle handle design allows easy fingertip operation and features a double key set and can be padlocked (padlock not included)
- The fail-safe closing mechanism utilizes a three-point stainless steel bullet latching system
- Adjust or add shelves to accommodate different size, or additional containers
- Optional polythene trays offer additional protection
- All cabinets meet NFPA Code 30 and OSHA standards



LYON[®]

Learn more at lyonworkspace.com or
call Customer Service at **800-323-0082**

FLAMMABLE SAFETY CABINETS



Specifications:

- 1 Full length continuous door hinges
- 2 All-welded 18-gauge, double wall construction with 1-1/2" of insulating air space offers fire resistant protection
- 3 Black, flush-mounted paddle handle design allows easy fingertip operation and features a double key set and can be padlocked (padlock not included). Slam-action closing mechanism utilizes a three-point stainless steel bullet latching system.
- 4 Heavy-duty ribbed, galvanized steel shelves deliver load capacity of 350 lbs. per shelf and are adjustable on 3" vertical centers
- 5 Ground wire connection deters static build-up (wire not included)
- 6 2" high leak-proof bottom pan
- 7 Yellow powder coat finish
- 8 Four, zinc-plated leveling legs
- 9 Screened flame arrester vents on both sides of cabinet (one high and one low) are threaded to accept standard 2" pipe for external exhaust
- 10 Self-Closing Doors - Latch holds door open when in use and will release to close door automatically when temperatures reach 165°F



All cabinets meet NFPA Code 30
and OSHA Requirements

LYON[®]

Learn more at lyonworkspace.com or
call Customer Service at **800-323-0082**